

# DA-45



## Specification

Thermal efficiency	
Uw*: Coefficient value for reference design	6,1* W/m <sup>2</sup> K
U factor*:	1,08* Btu/h·ft <sup>2</sup> ·F
*:	Reference window with dimensions of 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name:	DA-45
Installation depth:	Frame: 54 mm   Sash: 45 mm
Number of chambers:	1
Thermal break:	none
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	Float 4 mm
Ug value:	5,8 W/m <sup>2</sup> K
Glazing Package Thickness:	Glazing thickness available from 4 to 34 mm

Sound insulation of available glazing:	Rw: from 31 to 42 dB
<b>Fittings</b>	
Type:	---
Hinges:	surface
Anti-theft protection:	anti-theft catches
Microventilation:	yes
Other:	Four-stage tilt and slide mechanism   Handle rotation lock with a lifter
<b>Handle</b>	
Colors:	---
Handle model:	1006
<b>Dimensions</b>	
Maximum window width - single sash:	1600 mm
Maximum window height - single sash:	2400 mm
Maximum window width - double sash with a movable post:	3000 mm
Maximum window height - double sash with a movable post:	2400 mm
Maximum sash area:	3 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg):	3500 x 2900 mm lub 2900 x 3500 mm

## Photos

