

## DDF-92 AL



## Specification

Thermal efficiency	
U <sub>w</sub> *: Coefficient value for reference design	0,86 W/m <sup>2</sup> K
U factor*:	0,12* Btu/h·ft <sup>2</sup> ·F
*:	Glass: 4/12/4/12/4/12/4; gas: argon; warm edge spacer; window size: 48 7/16in x 58 4/16in (1230 mm x 1480 mm)
Profile	
Profile name:	DDF-92
Installation depth:	106 mm
Number of chambers:	n/a
Thermal break:	n/a
Number of seals:	3
Glass	
Glazing package:	4/16/4/16/4
U <sub>g</sub> value:	0,5 W/m <sup>2</sup> K
Glazing Package Thickness:	44 mm
Sound insulation of available glazing:	---
Fittings	

Type:	---
Hinges:	surface
Anti-theft protection:	1 anti-theft catch
Microventilation:	yes
Other:	---
<b>Handle</b>	
Colors:	---
Handle model:	1006
<b>Dimensions</b>	
Maximum window width - single sash:	1500 mm
Maximum window height - single sash:	2550 mm
Maximum window width - double sash with a movable post:	2080 mm
Maximum window height - double sash with a movable post:	2550 mm
Maximum sash area:	3 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg):	3500 x 2900 mm lub 2900 x 3500 mm

## Photos

